

Key Features

- * Sunlight Readable
- * High Contrast Ratio
- * Wide Temperature
- * Low Power Consumption
- * Optional Touch System
- * WUXGA+



JS400LPNN / JS400LKNN

Model	JS400LPNN	JS400LKNN
Display Type	LCD + LED Driver	LCD + LED Driver + AD/OSD Board
LCD Display	40" TFT LCD Module	40" TFT LCD Module
Base Panel Supplier	SS Display	SS Display
Base Panel Model	LTI400HA02	LTI400HA02
Display Color	8-bits, 16.7M colors	8-bits, 16.7M colors
Display Area	885.6 x 498.15 mm	885.6 x 498.15 mm
Brightness	1,200 cd/m ²	1,200 cd/m ²
Resolution	1920 x 1080 (WUXGA+)	1920 x 1080 (WUXGA+)
Contrast Ratio	3,000 : 1	3,000 : 1
Pixel Pitch (mm)	0.46125 x 0.46125	0.46125 x 0.46125
Viewing Angle	89°/89°(H) 89°/89°(V)	89°/89°(H) 89°/89°(V)
Response Time	21ms (Tr+Tf)	21ms (Tr+Tf)
Sync	LVDS	LVDS
Power Consumption	TBD	TBD
Temperature	Operation 0°C~+50°C Storage -20°C~+60°C	Operation 0°C~+50°C Storage -20°C~+60°C
Dimension(WxHxD)mm	931.00 x 543.00 x 129.00	931.00 x 543.00 x 129.00
Lamp Lifetime (HR)	50,000	50,000
Control(AD) Board (Optional)	None	N/A
OSD Button	None	5 Key
OSD Menu	Brightness Contrast H/V Position Color Phase Clock...	
LED Driver	JL400	JL400
Weight	12,500 g	12,600 g
Optional	Transflective	Glass Bonding Touch

Specifications are subject to change without notice

Control(AD) Board (Optional)	Standard	VGA + DVI + Audio(Optional)
	Option	VGA + DVI + Composite + S-Video + Audio(Optional)
OSD Button	5 Key	Power Switch Select(+,-) Down Up Menu